




## SS213/SS272 uPVC PIPES

COMPLY WITH BS5255, BS4660









## STANDARD SPECIFICATIONS

Pipe Standard	SS213:1983   SS272:201			
Standard Length	5.8 meters			
Standard Color	White (SS213), Golden Brown (SS272)			
Material	uPVC			

## FLUID AND APPLICATIONS

SS213 PIPES: Commonly used for sanitation application and are used in apartments, industrial & commercial buildings. It is also suitable for application such as rainwater down pipes and for other water discharge purposes.

— SS272 PIPES: Commonly laid underground as sewer or
\_ subsoil drainage for parks and fields. The golden brown gloss finish fabricated color reduces heat absorptions.

## **DIMENSIONS**

SS213:1983 BS5255:1989

			Î	Î		
SKU	DN (mm)	D (mm)	d (mm)	T (mm)	WEIGHT (kg)	
PIP213035N	35	36.2	32.0	2.1	2	
PIP213042N	42	42.8	38.2	2.3	3	
PIP213050N	50	55.7	50.9	2.4	4	
PIP213080N	80	82.3	76.3	3.0	7	
PIP213100N	100	110.0	103.6	3.2	10	
PIP213150N	150	160.0	152.0	4.0	18	
SS272:1983 BS4660:2000						
PIP272100N	100	110.0	103.6	3.2	10	
PIP272150N	150	160.0	152.0	4.0	18	