

OIL FILLED PRESSURE GAUGE























H	K	UI	Ν	ı	٧	II	E'	V١	/

COMPONENT PARTS					
ITEM	PARTS	MATERIAL			
1	Case	Steel			
2	Viewing Lens	ABS			
3	Screw	Stainless Steel			
4	Socket	Brass			
5	Indicator Needle	Aluminium Black Painted			
6	Dial	Aluminium White painted with Black/ Red marking			
7	Stop Pin	Aluminium			
8	Oil	Glycerin			



STANDARD SPECIFICATIONS

SKU	SIZE(mm)	L(mm)	W(mm)	H1(mm)	H2(mm)	Е	PCS/CTN	OPERATING PRESSURE
PG0503000F	50	52	27	71	51	1/4"BSPT	100	
PG0653000F	65	62	28.2	81	60.8	1/4"BSPT	50	0-300Psi kg/cm² 20bar
PG0803000F	80	81	32	112	80	3/8"BSPT	70	0-300FSI KY/CIII- ZUDAI
PG1003000F	100	109	37	136.6	99	1/2"BSPT	40	
PG1003500F	100	109	37	136.6	99	1/2"BSPT	40	0-350Psi kg/cm² 25bar

^{*} When releasing of pressure, please open release valve slowly to avoid pin out of calibration.