




FULL FACE FLANGE EPDM RUBBER GASKET (NORIKA) FOR POTABLE WATER

COMPLY WITH BS 4504 PN16
SS270:2015
SS375:2015



STANDARD SPECIFICATIONS

MATERIAL	EPDM
RUBBER HARDNESS	66-75
OPERATING TEMPERATURE	-15~+85°C

CROSS SECTIONAL VIEW

DIMENSIONS

SKU	SIZE (mm)	D1 (mm)	PCD (mm)	Nos OF HOLES	d (mm)	D2 (mm)	T (mm)	WEIGHT (kg)	PCS/CTN
RFGN050-PUB-F	50	50	125	4	18	165	4.4	0.095	250
RFGN065-PUB-F	65	65	145	4	18	185	4.4	0.105	200
RFGN080-PUB-F	80	80	160	8	18	200	4.4	0.120	200
RFGN100-PUB-F	100	100	180	8	18	220	4.5	0.155	150
RFGN150-PUB-F	150	150	240	8	22	285	4.5	0.255	100
RFGN200-PUB-F	200	200	295	12	22	340	5.4	0.450	35
RFGN250-PUB-F	250	250	355	12	26	405	6.0	0.595	35
RFGN300-PUB-F	300	290	410	12	26	460	6.0	0.750	25